

Technical Data Sheet

TOGIS – Binder Nr. 8160

Application range	For color and viscosity adjustment of TOGIS Textile Printing Ink No. 8100 – 8159.
Technical qualities	Water-dilutable.
Full declaration	Water, polysaccharides, chitosan, acetic acid and safflower oil.
Application method	Stir thoroughly before use. Add max. 5% of water to adjust the consistency. For color adjustment, mixable with all colors in any ratio.
Coverage	Depending on the desired color and can only be determined by test application.
Cleaning	Clean tools immediately after use with water. For dried product residues, use TOGIS Cleaning Concentrate No. 8165/8164 (for black and indigo blue).
Specific gravity	Approximately 1.00 g/ml.
Safety advice	P102 Keep out of the reach of children.
Disposal	According to locally regulated laws.
Container sizes	1 kg; 2,5 kg; 10 kg.
Storage	Cool, but frost-free and dry. Shelf life: unopened at least 2 years. Close opened product tightly.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

December 2017

LIVOS Plant Chemistry D-29559 Wrestedt OT Emern • Tel. +49 5825 / 88-0 • Fax 88-60 • www.livos.de • info@livos.de