

Technical Data Sheet

TOGIS – Thickener No. 8161

Application range	To adjust higher viscosities of TOGIS-Textile Printing Ink No. 8100 – 8170. Application quantity up to 1% by weight.
Full declaration	Starch.
Application method	Intersperse slowly, while stirring into the ready-made TOGIS Textile Printing Ink and stir for about 20 minutes until the Thickener is free of lumps. The addition of about 0.1 wt. % of TOGIS-Thickener to the ink increases the viscosity by approximately 10%.
Safety advice	P102 Keep out of the reach of children.
Disposal	According to locally regulated laws.
Container sizes	0.4 kg; 2.0 kg.
Storage	Cool, but frost-free and dry. Shelf life: unopened at least 5 years. Close opened product tightly.
Important information	The addition of more than 1 wt. % limits the wash resistance and application of the color. The cleaning of the equipment is more laborious.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

December 2017

LIVOS Plant Chemistry D-29559 Wrestedt OT Emern · Tel. +49 5825 / 88-0 · Fax 88-60 · www.livos.de · info@livos.de